

537,078

Rec'd PCT/PTO 01 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/051060 A1

(51) International Patent Classification⁷:

F02B 1/12

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/EP2003/050936

(22) International Filing Date: 3 December 2003 (03.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02258334.8 3 December 2002 (03.12.2002) EP(71) Applicant (*for all designated States except US*): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): CRACKNELL, Roger, Francis [GB/GB]; Pool Lane, Ince, Chester, Cheshire CH2 4NU (GB).

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



A1

WO 2004/051060

(54) Title: PROCESS AND APPARATUS FOR CONTROLLING THE PERFORMANCE OF A HOMOGENEOUS CHARGE COMPRESSION IGNITION (HCCI) ENGINE

(57) **Abstract:** The invention relates to a process for controlling the performance of a homogeneous charge compression (HCCI) engine in a vehicle having a hydrocarbon fuel reservoir which process comprises adjusting the octane or cetane number of hydrocarbon fuel being supplied to the HCCI engine by: a) converting a portion of hydrocarbon fuel from the hydrocarbon fuel reservoir to synthesis gas; b) converting synthesis gas produced in step (a) to a mixture of hydrocarbons having an octane number less than or a cetane number higher than that of the hydrocarbon fuel of the hydrocarbon fuel reservoir using a Fischer Tropsch process; c) delivering (i) a portion of hydrocarbon fuel from the hydrocarbon fuel reservoir and (ii) a portion of the mixture of hydrocarbons produced in step (b) to the HCCI engine; and d) varying the amounts of (i) and (ii) in step (c) in order to adjust the octane or cetane number of the hydrocarbon fuel being supplied to the HCCI engine. Apparatus suitable for carrying out this process is also disclosed.